

SF-828

MULTIFUNCTIONAL BONDING MACHINE 多功能粘合机



INCREDIBLE SOLUTION

- Workable on 2D and 3D construction
- Both Straight and Curve Seam
- Uniform Temperature
- Stretch Fabric Ready

不可思议的解决方案

- 适用于平面与3D立体造型工艺
- 可轻松应对于直线与弯曲位
- 预置弹性面料处理程序
- 精准控制加热温度

HIGHLIGHTING FEATURES

- Multi-heater Ensure Adhesive Strength
- Differential Speed Top/Bottom Roller
- Color Touch Screen Interface
- Automatic Tensioning Device
- Good for All Fabric
- Ergonomic
- Seam Sealing, Overlapping, Heming And Piding, Four In One Function

显著特点

- 多重加热器确保粘合强度
- 彩色触摸屏界面
- 上下轮可差速
- 自动送带装置
- 适合所有面料
- 人体工程学
- 贴带, 包边, 折边, 叠骨, 四合一功能

SPECIFICATIONS

| Power Supply | 电压 | | AC 220V 50/60Hz, 1Φ |
|----------------------------|--------|------------|---------------------|
| Heater Power | 功率 | (W) | 2680 |
| Compressed Air | 压缩空气 | (Mpa) | > 0.4 |
| Maximum Speed | 最大工作速度 | (M/min) | 5 |
| Maximum Nozzle Temperature | 最高风嘴温度 | (°C) | 350 |
| Maximum Roller Temperature | 最高滚轮温度 | (°C) | 250 |
| Working Width | 工作宽度 | (mm) | 6 ~ 20 |
| Dimensions | 外形 | LxWxH (mm) | 1220 x 700 x 1450 |
| Net Weight | 净重 | (kg) | 130 |

规格



SYMBOLS 标志



**TOP & BOTTOM
DIFFERENTIAL
FEED ROLLER**



TAPE CUTTER



EDGE TRIMMER




VACUUM SUCTION



HOT AIR



CHUTE HEAT



PROGRAM CONTROL




**BLACK & WHITE
DISPLAY WITH
TOUCH SCREEN**




**COLOUR DISPLAY
WITH TOUCH SCREEN**




**DISPLAY
PUSH BUTTON**




**UPPER MOLD
MOVES DOWN**



**BOTTOM MOLD
MOVES UPSIDE**



**HEAT ON
UPPER MOLD**



**HEAT ON
BOTTOM MOLD**




HEAT & COOL



**MANUAL MOVEMENT
UPPER OR LOWER MOLD**




**AUTO MOVEMENT
UPPER OR LOWER MOLD**



SWING ARM



TAPE FEEDER



**SCISSOR UPPER
MOLD MOVEMENT**



ULTRASONIC



www.lidermaq.com
ventas@lidermaq.net

H&H

SINCE 1993

H&H ASIA GROUP LTD.

Room 1117, 11/F, Asia Trade Centre, 79 Lei Muk Road, Kwai Chung, N.T., Hong Kong

高科美亚有限公司

香港新界葵涌梨木道79号亚洲贸易中心11楼1117室

sales@hh.com.hk | www.hh.com.hk