

TD-200 PORTABLE ROLLER SPOTTING STATION

手持滚轮式定位器



INCREDIBLE SOLUTION

- Modular Design of Controller and Heating Roller
- Consistent Temperature
- Uniform Temperature
- Simple to Use

不可思议的解决方案

- 模块化设计控制器和发热轮
- 精准控制加热温度
- 发热轮温度平均
- 操作简单易用

HIGHLIGHTING FEATURES

- Heating Roller Can Suspended Placed
- Digital Temperature Controller
- Compact Body Size

显著特点

- 体积小巧，结构紧凑
- 发热滚轮可悬挂放置
- 数字式温度控制

SPECIFICATIONS

规格

Power Supply	电压		AC 220V 50/60Hz, 1Φ
Heater Power	功率	(W)	200
Maximum Temperature	最高加热温度	(°C)	260
Roller Diameter	滚轮直径	(mm)	30
Dimensions	外形	LxWxH (mm)	170 x 120 x 260
Net Weight	净重	(kg)	2



H&H

SINCE 1993

H&H ASIA GROUP LTD .

Room 1117, 11/F, Asia Trade Centre, 79 Lei Muk Road, Kwai Chung, N.T., Hong Kong

高科美亚有限公司

香港新界葵涌梨木道79号亚洲贸易中心11楼1117室

sales@hh.com.hk | www.hh.com.hk



LIDERMAQ

www.lidermaq.com
ventas@lidermaq.net